


SAMSON

SHP Series

Lug/Snap-in Terminal Type(插入/自立型), Wide Temperature(寬溫度)

FEATURES

- Highly reliable capacitors that withstand under high ripple current.
- Two or three dimensions with same ratings.
- Aluminum case designed explosion-proof vent.
- Best for switching power supplies.



SPECIFICATIONS

Item	Performance Characteristics													
Operating Temperature Range	-40 to +105°C				-25 to +105°C									
Rated Working Voltage Range	10 to 100V				160 to 450V									
Nominal Capacitance Range	47 to 56000μF													
Capacitance Tolerance	±20% (120Hz, +20°C)													
Leakage Current	I ≤ 3 √CV (μA) after 5 minutes application of rated working voltage at +20°C													
Dissipation Factor tan δ (120Hz, +20°C)	Working Voltage (V)	10	16	25	35	50	63	80	100					
	tan δ (max.)	0.55	0.50	0.45	0.35	0.30	0.30	0.25	0.20					
	Working Voltage (V)	160 ~ 220	250	315 ~ 450										
	tan δ (max.)	0.15	0.15	0.15										
	For capacitance value > 33000μF, add following calculated value: $\frac{(\text{rated capacitance}) - 33000\mu\text{F}}{10000\mu\text{F}} \times 0.1$													
Low Temperature Characteristics	Impedance ratio max. at 120Hz													
	Working Voltage (V)	10	16	25	35	50	63	80	100					
	Z-25°C / Z+20°C	6	6	6	6	4	3	3	3					
	Z-40°C / Z+20°C	15	15	15	10	8	6	6	6					
	Working Voltage (V)	160	200 ~ 220	250	315 ~ 385	400	450							
	Z-25°C / Z+20°C	8	8	8	8	8	8							
	Z-40°C / Z+20°C	-	-	-	-	-	-							
High Temperature Loading	Test conditions After 2000 hours application of rated voltage at +105°C the capacitor shall meet the following limits					Post test requirements at +20°C Leakage current : ≤ Initial specified value Cap. change : within ±20% of initial measured value tan δ : ≤ 200% of initial specified value								
Shelf Life	At 105°C no voltage applied after 1000 hours the capacitors shall meet the following limits Leakage current : ≤ Initial specified value Cap. change : within ±15% of initial measured value tan δ : ≤ 150% of initial specified value													
Others	JIS C - 5141 JIS C - 5102													

RIPPLE CURRENT MULTIPLIER

Temperature Coefficient	Frequency Coefficient
1) Maximum rms ripple current at 120Hz, 105°C are given in the table.	3) Frequency multiplying factor:
2) Temperature multiplying factor: Where capacitors are operated at temperature other than 105°C, the maximum ripple current must be multiplied by the figure shown in the table below.	If capacitors are used to filter circuits at a frequency other than 120Hz, the maximum ripple current must be multiplied by the figure shown in the table below.
Temperature(°C)	Freq.(Hz)
20 ~ 45	60
65	120
85	1K
105	10 ~ 50K
Factor	10 ~ 100V
	160 ~ 250V
	315 ~ 450V
2	0.9
1.89	1.0
1.52	
1.0	
	0.8
	1.0
	1.25
	1.15
	1.47
	1.30
	1.47

SHP Series

Lug/Snap-in Terminal Type(插入/自立型), Wide Temperature(寬溫度)

DIMENSIONS									
Voltage (Code)		10V		16V		25V		35V	
Cap.(μ F)	Code	Case Size	Ripple Current						
2700	278							20 x 25	1.29
3300	338							20 x 30	1.57
3900	398					20 x 25	1.58	22 x 25	1.45
4700	478					20 x 30	1.65	20 x 35	1.78
5600	568			20 x 25	1.68	22 x 30	1.80	22 x 30	1.69
6800	688	20 x 25	1.31	20 x 30	1.80	20 x 40	2.11	22 x 40	2.41
8200	828	20 x 30	1.59	20 x 35	2.08	22 x 35	2.09	25 x 35	2.31
10000	109	20 x 30	1.88	22 x 30	2.10	25 x 25	1.87	30 x 25	2.31
12000	129	22 x 25	1.77	25 x 25	2.05	30 x 30	2.16	30 x 30	2.75
15000	159	20 x 35	2.18	22 x 35	2.31	22 x 45	2.65	25 x 45	3.05
18000	189	22 x 30	2.10	25 x 30	2.30	25 x 40	2.81	30 x 40	3.23
22000	229	25 x 25	1.94	30 x 25	2.30	30 x 30	2.74	35 x 30	3.19
27000	279	20 x 40	2.27	22 x 40	2.68	25 x 45	3.27	30 x 45	3.72
33000	339	22 x 35	2.23	25 x 35	2.58	30 x 35	3.13	35 x 35	3.67
39000	399	25 x 30	2.10	30 x 30	2.57	35 x 30	3.26		
47000	479	22 x 40	2.41	22 x 50	3.20	30 x 40	3.56	35 x 40	4.37
56000	569	25 x 30	2.34	25 x 40	3.16	35 x 35	3.84		
		30 x 25	2.25	30 x 30	2.98				
		22 x 45	2.58	25 x 45	3.36	30 x 45	4.04	35 x 45	4.92
		25 x 35	2.54	30 x 35	3.30	35 x 35	3.75		
		30 x 30	2.50	35 x 30	3.25				
		22 x 50	3.17	25 x 50	3.85				
		25 x 40	3.07	30 x 40	3.80				
		30 x 30	2.95	35 x 35	3.93				
		25 x 45	3.39	30 x 45	4.30				
		30 x 35	3.33	35 x 35	4.27				
		35 x 30	3.21						
		30 x 40	3.70	30 x 50	4.81				
		35 x 35	3.68	35 x 40	4.80				
		30 x 45	4.22						
		35 x 40	4.16	35 x 45	5.53				
		35 x 50	5.00						

Maximum Allowable Ripple Current (A rms) at 105°C 120Hz

Case Size ϕ D x L(mm)

SAMSON

SHP Series

Lug/Snap-in Terminal Type(插入/自立型), Wide Temperature(寬溫度)

DIMENSIONS										
Voltage (Code)		50V		63V		80V		100V		
Cap.(μ F)	Code	Case Size	Ripple Current							
560	567							20 x 25	0.95	
680	687							20 x 30	1.15	
820	827					20 x 25	1.04	22 x 25	1.09	
1000	108			20 x 25	1.10	20 x 30	1.24	20 x 35	1.31	
						22 x 25	1.19	22 x 30	1.32	
								25 x 25	1.45	
1200	128			20 x 30	1.20	20 x 35	1.43	20 x 40	1.61	
				22 x 25	1.20	22 x 30	1.44	22 x 35	1.69	
						25 x 30	1.68			
1500	158	20 x 25	1.15	20 x 35	1.47	20 x 35	1.57	22 x 40	1.97	
				22 x 30	1.47	22 x 30	1.59	25 x 35	1.98	
						25 x 25	1.59	30 x 25	1.95	
1800	188	20 x 30	1.39	20 x 35	1.58	20 x 40	1.77	22 x 45	2.23	
		22 x 25	1.34	22 x 30	1.58	22 x 35	1.79	25 x 40	2.20	
2200	228	20 x 35	1.60	20 x 40	1.80	22 x 40	2.03	25 x 45	2.53	
		22 x 30	1.60	22 x 35	1.82	25 x 35	1.98	30 x 35	2.55	
2700	278	20 x 35	1.73	22 x 40	2.07	22 x 45	2.39	25 x 50	2.82	
		22 x 30	1.70	25 x 35	2.11	25 x 40	2.35	30 x 40	2.86	
		25 x 25	1.70	30 x 25	1.72	30 x 30	2.35	35 x 35	2.89	
3300	338	20 x 40	1.97	22 x 45	2.33	25 x 45	2.64	30 x 45	3.30	
		22 x 35	1.97	25 x 35	2.27	30 x 35	2.61	35 x 35	3.25	
		25 x 30	1.88	30 x 30	2.24	35 x 30	2.47			
3900	398	22 x 40	2.22	25 x 40	2.51	25 x 50	2.92	30 x 50	3.60	
		25 x 30	2.20	30 x 35	2.55	30 x 40	2.82	35 x 40	3.67	
		30 x 25	1.95			35 x 30	2.97			
4700	478	22 x 45	2.43	25 x 50	2.91	30 x 45	3.34	35 x 45	3.80	
		25 x 35	2.43	30 x 40	2.86	35 x 35	3.38			
		30 x 30	2.25	35 x 30	2.80					
5600	568	22 x 50	2.75	30 x 40	3.22	30 x 50	3.80	35 x 50	4.05	
		25 x 40	2.72	35 x 35	3.20	35 x 40	3.80			
		30 x 30	2.64							
6800	688	25 x 45	3.30			35 x 45	3.90			
		30 x 35	3.30	30 x 50	3.65					
		35 x 30	3.25	35 x 40	3.65					
8200	828	30 x 40	3.60	35 x 45	4.04	35 x 50	4.20			
10000	109	35 x 35	3.60							
10000	109	30 x 50	4.05	35 x 50	4.48					
12000	129	35 x 40	4.04							
15000	159	35 x 45	4.56							
15000	159	35 x 50	4.77							

Maximum Allowable Ripple Current (A rms) at 105°C 120Hz

Case Size ϕ D x L(mm)

SHP Series

Lug/Snap-in Terminal Type(插入/自立型), Wide Temperature(寬溫度)

DIMENSIONS									
Voltage (Code)		160V		180V		200V		220V	
Cap.(μ F)	Code	Case Size	Ripple Current						
180	187							20 x 25	0.81
220	227			20 x 25	0.81	20 x 25	0.83	20 x 30	0.94
270	277	20 x 25	0.87	20 x 30	0.95	20 x 30	0.97	22 x 25	0.94
				22 x 25	0.97	22 x 25	0.99	20 x 35	1.10
								22 x 30	1.09
330	337	20 x 30	1.02	20 x 35	1.09	20 x 35	1.17	20 x 40	1.18
		22 x 25	1.03	22 x 30	1.13	22 x 30	1.20	22 x 35	1.24
390	397	20 x 35	1.15	20 x 35	1.28	20 x 40	1.27	20 x 45	1.33
		22 x 30	1.17	22 x 30	1.32	22 x 35	1.30	22 x 35	1.30
470	477	20 x 40	1.25	20 x 40	1.34	22 x 40	1.44	22 x 40	1.41
		22 x 30	1.28	22 x 35	1.39	25 x 30	1.44	25 x 30	1.39
		25 x 25	1.29	25 x 30	1.43	30 x 25	1.48	30 x 25	1.37
560	567	22 x 35	1.45	22 x 40	1.56	22 x 45	1.60	22 x 45	1.60
		25 x 30	1.49	25 x 30	1.53	25 x 35	1.60	25 x 35	1.56
		30 x 25		30 x 25	1.56	30 x 30	1.60	30 x 30	1.61
680	687	22 x 40	1.64	22 x 45	1.76	22 x 50	1.75	25 x 40	1.75
		25 x 35	1.70	25 x 35	1.76	25 x 40	1.76	30 x 35	1.76
		30 x 25	1.63	30 x 30	1.74	30 x 30	1.74	35 x 30	1.72
820	827	22 x 45	1.85	22 x 50	1.97	25 x 45	2.10	25 x 45	1.97
		25 x 40	1.92	25 x 40	1.99	30 x 35	2.11	30 x 40	2.06
		30 x 30	1.91	30 x 30	1.93	35 x 30	2.10	35 x 30	1.95
1000	108	25 x 45	2.17	25 x 45	2.24	25 x 50	2.36	30 x 45	2.44
		30 x 35	2.19	30 x 35	2.24	30 x 40	2.40	35 x 35	2.20
		35 x 30		35 x 30	2.20	35 x 35	2.30		
1200	128	25 x 50	2.43						
		30 x 40	2.48	30 x 40	2.53	30 x 45	2.69	35 x 40	2.37
		35 x 30	2.25	35 x 35	2.54	35 x 35	2.53		
1500	158	30 x 45	2.82	30 x 50	3.03	35 x 40	2.97	35 x 45	2.64
		35 x 35	2.62	35 x 40	2.91				
1800	188	30 x 50	3.13	35 x 45	3.25	35 x 50	3.45		
		35 x 40	2.97						
2200	228	35 x 45	3.34	35 x 50	3.62				

Maximum Allowable Ripple Current (A rms) at 105°C 120Hz

Case Size φD x L(mm)

SAMSON

SHP Series

Lug/Snap-in Terminal Type(插入/自立型), Wide Temperature(寬溫度)

DIMENSIONS

Voltage (Code)		250V		315V		350V		385V	
Cap.(μ F)	Code	Case Size	Ripple Current						
56	566							20 x 25	0.37
68	686			20 x 25	0.41	20 x 30	0.44	20 x 30	0.44
								22 x 25	0.45
								20 x 30	0.50
82	826			20 x 25	0.39	20 x 30	0.45	22 x 30	0.52
				20 x 30	0.45	20 x 35	0.51	20 x 35	0.56
						22 x 25	0.53	22 x 30	0.58
100	107			20 x 30	0.45	25 x 25	0.57	25 x 25	0.57
						20 x 35	0.59	20 x 40	0.66
						22 x 30	0.61	22 x 35	0.68
120	127			22 x 25	0.56	25 x 25	0.62	25 x 30	0.68
						20 x 35	0.64	20 x 40	0.70
						22 x 30	0.66	22 x 40	0.79
150	157	20 x 25	0.71	25 x 25	0.65	22 x 35	0.73	25 x 30	0.78
				25 x 30	0.71	25 x 30	0.73	30 x 25	0.75
						30 x 25	0.81	30 x 30	0.88
180	187			20 x 30	0.82	22 x 40	0.89	22 x 45	0.89
				22 x 25	0.84	22 x 35	0.85	25 x 30	0.86
						25 x 30	0.95	25 x 45	1.01
220	227			22 x 30	0.97	25 x 30	0.98	25 x 40	1.00
				25 x 25	1.09	30 x 25	1.03	30 x 30	1.00
						30 x 30	1.08	30 x 40	1.13
270	277			20 x 40	1.11	22 x 45	1.01	30 x 45	1.14
				25 x 30	1.15	25 x 35	0.98	35 x 30	1.10
						30 x 30	1.08	35 x 35	1.26
330	337			22 x 40	1.26	22 x 50	1.14	30 x 45	1.31
				25 x 30	1.26	25 x 40	1.12	35 x 35	1.32
						30 x 35	1.21	35 x 30	1.18
390	397			22 x 45	1.41	25 x 45	1.31	30 x 50	1.48
				25 x 35	1.42	30 x 35	1.30	35 x 40	1.48
						35 x 30	1.23	35 x 35	1.39
470	477			22 x 50	1.58	30 x 40	1.53	35 x 45	1.76
				25 x 40	1.61	35 x 35	1.47	30 x 45	1.57
						30 x 30	1.61	35 x 35	1.50
560	567			25 x 45	1.80	30 x 45	1.65	35 x 50	1.95
				30 x 35	1.84	35 x 40	1.66	35 x 40	1.69
						35 x 40	1.75		
680	687			25 x 50	2.03				
				30 x 40	2.09	35 x 45	1.96	35 x 45	1.96
						35 x 45	2.19		
820	827			30 x 45	2.35				
				35 x 35	2.26				
1000	108			30 x 50	2.64				
				35 x 40	2.57				
1200	128			35 x 45	2.88				

Maximum Allowable Ripple Current (A rms) at 105°C 120Hz

Case Size ϕ D x L(mm)

SHP Series

Lug/Snap-in Terminal Type(插入/自立型), Wide Temperature(寬溫度)

DIMENSIONS

Voltage (Code)		400V		420V		450V		
Cap.(μ F)	Code	Case Size	Ripple Current	Case Size	Ripple Current	Case Size	Ripple Current	
47	476					20 x 25	0.36	
56	566	20 x 25	0.40	20 x 25	0.40	20 x 30	0.41	
						22 x 25	0.42	
68	686	20 x 30	0.48	20 x 30	0.48	20 x 35	0.47	
		22 x 25	0.49	22 x 25	0.50	22 x 30	0.50	
82	826	20 x 30	0.54	20 x 35	0.53	20 x 40	0.53	
		22 x 30	0.56	22 x 30	0.56	22 x 35	0.56	
100	107	20 x 35	0.60	20 x 35	0.58	22 x 40	0.64	
		22 x 30	0.62	22 x 30	0.63	25 x 30	0.63	
		25 x 25	0.61	25 x 25	0.63	30 x 25	0.67	
120	127	20 x 40	0.71	20 x 45	0.71	22 x 45	0.72	
		22 x 35	0.73	22 x 35	0.73	25 x 35	0.71	
		25 x 30	0.73	25 x 30	0.72	30 x 30	0.77	
		30 x 25	0.75					
150	157	22 x 40	0.85	22 x 45	0.86	22 x 50	0.80	
		25 x 35	0.85	25 x 35	0.83	25 x 40	0.82	
		30 x 25	0.79	30 x 25	0.83	30 x 30	0.85	
180	187	22 x 45	0.95	22 x 50	1.02	25 x 45	0.93	
		25 x 35	0.92	25 x 40	0.94			
		30 x 30	0.95	30 x 30	0.95	30 x 35	0.97	
				35 x 25	0.90			
220	227	22 x 50	1.08	25 x 45	1.13	25 x 50	1.05	
		25 x 40	1.05	30 x 35	1.09	30 x 40	1.10	
		30 x 35	1.24	35 x 30	1.05	35 x 30	1.01	
270	277	25 x 50	1.29	25 x 50	1.37	30 x 45	1.25	
		30 x 40	1.30	30 x 40	1.25	35 x 35	1.26	
		35 x 30	1.18	35 x 35	1.25			
330	337	30 x 45	1.47	30 x 45	1.49	30 x 50	1.42	
		35 x 35	1.41	35 x 35	1.42	35 x 40	1.44	
390	397	30 x 50	1.64	30 x 50	1.67	35 x 45	1.61	
		35 x 40	1.59	35 x 40	1.61			
470	477	35 x 45	1.87	35 x 45	1.86	35 x 50	1.80	
560	567	35 x 50	2.09					

Maximum Allowable Ripple Current (A rms) at 105°C 120Hz

Case Size φD x L(mm)